



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Installation guide Rack mounting brackets User manual
--------------------	---

Physical

Cable length	2.50 M
Colour	Black
Depth	10.8 Cm
Height	4.4 Cm
Net weight	2.27 Kg
Width	44.5 Cm

Input

[In] rated current	16 A
Permissible voltage	200...240 V
Input current limits	20 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Plug standard	IEC 60320 C20
Input voltage	200 V 208 V 230 V

Output

Number of power socket outlets	8 IEC 60320 C13
--------------------------------	-----------------

Conformance

Product certifications	CUL listed CE CSA GOST IRAM MIC UL listed VDE VCCI
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 UL 60950

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 M

Packing Units

Package 1 Weight	3.45 Kg
Package 1 Height	7 Cm
Package 1 width	47 Cm
Package 1 Length	34.3 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**