



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Documentation CD Installation guide Rack mounting brackets
--------------------	--

Physical

Cable length	3.05 M
Colour	Black
Depth	11.4 Cm
Height	8.9 Cm
Net weight	4.5 Kg
Width	44.5 Cm

Input

Permissible voltage	220...240 V
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 32 A 2P + E
Input voltage	200 V 208 V 230 V

Output

Number of power socket outlets	16 IEC 60320 C13
--------------------------------	------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Conformance

Product certifications	CE GOST IRAM MIC VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 M

Packing Units

Package 1 Weight	6.55 Kg
Package 1 Height	14 Cm
Package 1 width	50.8 Cm
Package 1 Length	36.8 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**