



Overview

Presentation	Tall enclosure with 48U spaces for additional equipment. Compact width to optimize data center space. For low to medium density server and networking applications.
Lead time	Usually in Stock

General

Provided equipment	<ul style="list-style-type: none"> Baying hardware Key(S) Keyed-alike doors and side panels Leveling feet Mounting hardware Pre-installed casters Side panels
--------------------	--

Physical

Maximum mounting depth	91.49 Cm
Number of rack unit	48U
Minimum mounting depth	19.1 Cm
Marking	<ul style="list-style-type: none"> 14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Colour	Black
Depth	107 Cm
Rack width	19"
Height	225.8 Cm
Net weight	138.23 Kg
Permanent permissible load	<ul style="list-style-type: none"> 1020.58 Kg dynamic 1700.97 Kg static
Width	60 Cm

Conformance

Standards	<ul style="list-style-type: none"> UL 2416 UL 60950-1 EIA-310E
-----------	---

Packing Units

Package 1 Weight	157.68 Kg
Package 1 Height	238.5 Cm
Package 1 width	75.2 Cm
Package 1 Length	115.6 Cm
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------

Product Life Status : **Commercialised**