



### General

Provided equipment	Documentation CD Installation guide Operations and maintenance manual
Air discharge option	Upflow Ducted
Air flow	755.12 l/s

### Physical

Colour	Black
Depth	25.4 cm
Height	191.8 cm
Net weight	77.27 kg
Width	73.7 cm

### Input

Number of cables	2
Input power	1200 W
Network frequency	50/60 Hz
Plug standard	IEC 60320 C14 NEMA 5-15P
Input voltage	100 V 120 V 200 V 208 V 230 V

### Conformance

Product certifications	CUL listed
------------------------	------------

CE  
UL listed  
VDE

---

Standards	EN 55022 class A EN 55024 FCC part 15 class A ICES-003 IEC 61000-3-2 IEC 61000-3-3
-----------	---

---

### Environmental

---

Ambient air temperature for operation	0...50 °C
Ambient air temperature for storage	0...50 °C
Relative humidity	0...95 %
Storage altitude	0.00...4572.00 m
Acoustic level	79 dBA

---

### Communications & Management

---

Control panel	Multifunction LCD status and control console
---------------	--

---

### Offer Sustainability

---

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Halogen content performance	Halogen free product

---

### Contractual warranty

---

Warranty	1 year (parts only)
----------	---------------------

---