



Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

General

Provided equipment	Installation guide Operations and maintenance manual
Air discharge option	Horizontal
Intake air option	Rear return
Air flow	1982.18 l/s
Minimum water inlet temperature	7 °C

Physical

Number of rack unit	42U
Colour	Black
Depth	109.5 cm
Height	199.1 cm
Net weight	210 kg
Width	30 cm

Input

Number of cables	2
Number of feeders	2
Input power	1900 W
Minimum circuit ampacity	15 A
Network frequency	50/60 Hz
Maximum overcurrent protection	15 A
Number of input connectors	1 hard wire 3-wire
Input voltage	208 V 220 V 230 V

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

Conformance

Product certifications	C-Tick CE GOST MEA VDE
Standards	EN 55022 class A EN 55024 EN 60950 IEC 60950 IEC 61000-3-2 IEC 61000-3-3

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity

Packing Units

Package 1 Weight	220 kg
Package 1 Height	211.8 cm
Package 1 width	74.6 cm
Package 1 Length	113.7 cm
Number of Units in Package 3	1

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	1 year (parts only)
----------	---------------------